

» Smart controls simplify desiccant drying

- Optimized performance
- Temperature and humidity display
- Humidistat and RH minimum setpoint to prevent overdrying
- Pints-per-day display

» 33% smaller than closest competitor

» The most versatile desiccant on the market

- Run on a single 120v circuit for basic operation or use 2 cords to optimize performance
- Highly portable operate on its back for low-clearance areas (great for crawlspaces!)
- Includes onboard storage for accessories

» Famous Dri-Eaz durability

- Sturdy Designed for everyday restoration use and abuse!
- PTC heaters deliver better efficiency, safety and longer life
- Best warranty in the industry

» Great for dense materials, hardwood floors and cooler environments

The simple tool for difficult drying.

ACCESSORIES INCLUDED:

- . Reactivation Out duct ring
- · Reactivation Out heat-resistant ducting, 6" diameter, 20 ft. length
- · Air inlet duct ring
- · Process air outlet adaptor assembly (optional: F536 - 16" layflat ducting)



ONBOARD STORAGE



SPCIFICATIONS:

MODEL F533 PROCESS AIR 395 CFM TESTED REACTIVATION AIR 65 cfm WATER REMOVAL 118 pints per day

(AT 80°F/60% RH) **DIMENSIONS (W × H × D)** $21.14 \times 33.13 \times 20.25$ in.

(Handle upright = 42. 250 in.) WEIGHT 95 lbs. | 43.1 kg

CONSTRUCTION Powder-coated steel POWER 120V / 60 HZ

AMPS (AT 80°F/60% RH) Circuit 1: 11.0; Circuit 2: 10.0 BEST IN INDUSTRY 7 years for the body LIMITED WARRANTY 2 years on the rotor

1 year parts & labor

XACTIMATE CODE WTRDHMD











