



MSDS Number: S712 Revision Date: April 26, 2012

Page 1 of 4

#### 1

# PRODUCT AND COMPANY IDENTIFICATION

### **Manufacturer**

Kärcher North America, Inc. Prochem 325 S. Price Road Chandler, AZ 85224

 Phone:
 480-899-7000

 Fax:
 480-786-9538

 Email:
 info@prochem.com

 Web:
 www.prochem.com

Product Name: Ultrapac Trafficlean Revision Date: April 26, 2012

MSDS Number: S712

For Chemical Emergency, Spill, Leak, Fire, Exposure Call: (800) 535-5053 [Infotrac]

# 2

#### HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation;

Target Organs: Eyes; Skin;

Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.

**Skin Contact:** May cause irritation. **Eye Contact:** May cause irritation.

**Ingestion:** Ingestion is not applicable route of entry for intended use.

NFPA: HMIS III:



GHS Precautionary Statements:

Health = 1, Fire = 2, Reactivity = 0 H1/F2/PH0


HMIS III			
HEALTH		1	
FLAMMABILITY 2			
PHYSICAL HAZARDS		0	
PERSONAL PROTECTION B   Safety Glasses, Gloves			

P102 - Keep out of reach of children.

P103 - Read label before use.

P233 - Keep container tightly closed.

P262 - Do not get in eyes, on skin, or on clothing.







MSDS Number: S712 Revision Date: April 26, 2012

Page 2 of 4

## 3

## **HAZARDS IDENTIFICATION**

#### Ingredients:

CAS #	Percent	Chemical Name
111-76-2	<3%	Ethylene Glycol Butyl Ether
112-34-5	<8%	Diethylene Glycol Butyl Ether

### **OSHA Regulatory Status:**

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

# FIRST AID MEASURES

Inhalation: If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.

**Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.

Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate

irrigation. Get immediate medical attention.

**Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious,

give two glasses of water. Seek medical attention.

#### 5

#### FIRE FIGHTING MEASURES

**Flash Point:** 183° F **Flash Point Method:** Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

## 6

# **ACCIDENTAL RELEASE MEASURES**

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

#### 7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid

spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.

Storage Requirements: Keep away from children. Store in cool/dry area; Keep container closed.

#### 8

### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering Controls:** Normal room ventilation is satisfactory for limited use.

Personal Protective Equip: HMIS PP, B | Safety glasses, Gloves





MSDS Number: S712 Revision Date: April 26, 2012

Page 3 of 4

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

## 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Caramel opaque

Physical State:LiquidOdor:MintSpec Grav./Density:9.48 lb/galSolubility:SolublepH:9.5VOC:0.096%

## 10 STABILITY AND REACTIVITY

**Stability:** Product is stable under normal conditions.

Conditions to Avoid: None known Materials to Avoid: None known

Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified

thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

### TOXICOLOGICAL INFORMATION

### **Toxicity Data:**

11

Ethylene glycol butyl ether 111-76-2

Oral (LD 50): 917 mg/kg - Rat

Inhalation (LC 50): 2900 mg/m3/7H - Rat

Skin irritation: Mild Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

Diethylene glycol butyl ether 112-34-5 Oral (LD 50): 5660 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Moderate Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

# 12 ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.





MSDS Number: S712 Revision Date: April 26, 2012

Page 4 of 4

13

## **DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local regulations.

14

#### TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

### 15

### **REGULATORY INFORMATION**

COMPONENT / (CAS/PERCENT) / CODES

\*Ethylene Glycol Butyl Ether (111762 <3%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

\*Diethylene Glycol Butyl Ether (112345 <8%) SARA313, TSCA, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TXAIR = TX Air Contaminants with Health Effects Screening Level WHMIS = Workplace Haz Mat Info Sys Canada

### 16

#### OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager Phone Number: [480] 899-7000