

Urine Rescue

MSDS Number: B114 Revision Date: August 16, 2010

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROCHEM Kärcher North America 325 S. Price Road Chandler, AZ 85224

Contact: Prochem

Telephone Number: 480-899-7000 FAX Number: 480-786-9538 E-Mail: info@prochem.com Web www.prochem.com

Product Name: Urine Rescue Revision Date: August 16, 2010

MSDS Number: B114

Emergency Telephone: (800) 535-5053 [Infotrac]

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation; Ingestion;

Target Organs: Eyes; Skin;

Inhalation: Nose and throat irritation; cough.

Skin Contact: Irritation and temporary whitening at contact area; risk of burns.

Eye Contact: Severe eye irritation, watering, redness and swelling of the eyelids; risk of serious or permanent

eye lesions.

Ingestion: Paleness and cyanosis of the face; severe irritation, risk of burns and perforation of the

gastrointestinal tract accompanied by shock. Excessive fluid in the mouth and nose, with risk of suffocation; risk of throat edema and suffocation; bloating of stomach, belching; nausea and

vomiting (bloody); cough; risk of chemical pneumonitis from product inhalation.

HMIS II-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0

HMIS Rating H2/F1/PH2®

NFPA-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas # Chemical Name

7722841 | <10% | Hydrogen peroxide

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.



Urine Rescue

MSDS Number: B114 Revision Date: August 16, 2010

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: Remove the subject from the contaminated area; move to fresh air. Consult with a physician in

case of respiratory symptoms.

Skin Contact: Remove contaminated shoes, socks and clothing; wash the affected skin with running water. If

irritation persists consult physician.

Eye Contact: Flush eyes immediately with running water for 15 minutes, while keeping the eyelids open.

Consult with a physician in all cases.

Ingestion: Consult with a physician immediately in all cases. Take to hospital.

General recommendations: In case of product splashing into the eyes and face, treat eyes first. Do not dry soiled clothing near an open flame or incandescent heat source. Submerge soiled clothing in water prior to drying.

FIRE FIGHTING MEASURES

Flash Point: >212°F
Flash Point Method: Closed Cup

5

Wear self contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Precautions: Observe the protection measures given in sections 5 and 8. Isolate the area. Avoid materials and products which are incompatible with the product (see section 10). If safe to do so, without exposing personnel, try to stop the spillage. In case of contact with combustible materials, avoid product drying out by dilution with water.

Cleanup methods: Keep all unnecessary personnel away. Eliminate sources of ignition. Prevent additional discharge of material. Prevent material from entering sewers, watercourses, or low areas. Contain and absorb spilled material with sand or earth. Do not use combustible materials such as sawdust. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

The National Transportation Safety Board (NTSB) and Federal Aviation Administration (FAA) have requested the following information be provided:

Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed. Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in a fire

7 HANDLING AND STORAGE

Handling Precautions: Operate in a well-ventilated area. Keep away from heat sources. Keep away from

incompatible products. Prevent all contact with organics. Use equipment and containers which are compatible with the substance. Never return unused product to storage container. Ensure an adequate supply of water is available in the event of an accident. Containers and equipment used to handle hydrogen peroxide should be used exclusively

for hydrogen peroxide.

Storage Requirements: Store out of the reach of children. Store in a ventilated, cool area; store away from heat

sources; keep away from incompatible products (see section 10). Keep away from combustible substances. Keep in container fitted with safety valve or vent. Keep in original packaging, closed. Regularly check the condition and temperature of the

containers.

Other precautions: Warn personnel of the dangers of the product. Follow the protective



N/D

N/D

8.69

Soluble

Urine Rescue

MSDS Number: B114 Revision Date: August 16, 2010

Page 3 of 4

measures given in section 8. Do not confine the product in the circuit, between closed valves, or in a container without a vent. Cloths used to apply or absorb product should be rinsed with water and stored in a fire-resistant container. Avoid contact with skin and eyes; do not breathe vapors. Wash hands thoroughly after handling.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use; keep away from heat and flame.

Boiling Point:

Solubility:

Freezing/Melting Pt.:

Spec Grav./Density:

Protective Equipment: HMIS PP, C | Goggles, Gloves, Apron

Exposure Guidelines/Other: Hydrogen Peroxide 7722-84-1 OSHA PEL 1 ppm/ 1.4 mg/m3

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear
Physical State: Liquid
Odor: None

pH: 3.0 - 5.0 **Vapor Pressure:** N/D

Vapor Density: N/D

VOC: 0 %

STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.

Conditions to avoid: Heat/Sources of heat; Contamination.

Materials to avoid (incompatability): Acids; Bases; Metals; Salts of metals; Reducing agents; Organic materials;

Flammable substances.

Hazardous Decomposition products: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids,

and other unidentified thermal decomposition products from this product or its

packaging.

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

10

Hydrogen Peroxide 7722-84-1

Oral (LD 50): 910 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe Eye irritation: Severe



Urine Rescue

MSDS Number: B114 Revision Date: August 16, 2010

Page 4 of 4

Sensitation: Not considered an occupational sensitizer

12

ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14

TRANSPORT INFORMATION

ORM-D (Other regulated material - Domestic)

Ship in accordance with 49 CFR parts 100-185.

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Hydrogen peroxide (7722841 <10%) EHS302, MASS, NJHS, OSHAPSM, OSHAWAC, PA, TXAIR, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

EHS302 = Extremely Hazardous Substance

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

OSHAPSM = OSHA Chemicals Requiring process safety management

OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

WHMIS= Workforce Hazardous Material Information System

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager Phone Number: [480] 899-7000