

Rust Remover

MSDS Number: B198

Revision Date: March 31, 2011

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROCHEM Kärcher North America 325 S. Price Road Chandler, AZ 85224

Contact: Prochem Telephone Number: 480-899-7000 FAX Number: 480-786-9538 E-Mail: info@prochem.com Web www.prochem.com

Product Name:	Rust Remover
Revision Date:	March 31, 2011
MSDS Number:	B198

Emergency Telephone: (800) 535-5053 [Infotrac]

2	HAZARDS IDENTIFICATION
Route of Entry:	Eyes; Skin; Inhalation; Ingestion;
Target Organs:	Eyes; Skin;
Inhalation:	Minimal respiratory tract irritation may occur with exposure to a large amount of material
Skin Contact:	May cause irritation.
Eye Contact:	May cause irritation.
Ingestion:	Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.
HMIS II-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0 HMIS® Rating H2/F1/PH0	

NFPA-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

CAS #	Percent	Chemical Name
144627	<10%	Oxalic acid
7664382	<5%	Phosphoric acid
112345	<4%	Diethylene Glycol Butyl Ether

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.



Rust Remover

MSDS Number: B198

Revision Date: March 31, 2011

Page 2 of 5

4	FIRST AID MEASURES
Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

Flash Point: Flash Point Method:

6

>212ºF Closed Cup

Wear self contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7 HANDLING AND STORAGE Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling. Storage Requirements: Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline product.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION	
Engineering Controls Protective Equipmen Exposure Guidelines	t: HMIS PP, B Safety glasses, Gloves	

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque off-white		
Physical State:	Liquid	Boiling Point:	N/D
Odor:	Sassafras	Freezing/Melting Pt.:	N/D
pH:	0.5-1.5	Solubility:	Soluble
Vapor Pressure:	N/D	Spec Grav./Density:	8.82
Vapor Density:	N/D		



Rust Remover

MSDS Number: B198

Revision Date: March 31, 2011

	Page 3 of 5	
10 STABILITY AND	DREACTIVITY	
Stability:	Product is stable under normal conditions.	
Conditions to avoid:	Open Flames, ignition points, heat sources	
Materials to avoid (incompatability):	None known	
Hazardous Decomposition products:	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.	
Hazardous Polymerization:	Will not occur.	
11 TOXICOLOGIC	AL INFORMATION	
Toxicity Data:		
Oxalic Acid 144-62-7		
Oral (LD 50): Not listed on RTECS		
Intraperitoneal (injection) 270 mg/kg - Mo	buse	
Inhalation (LC 50): Not listed on RTECS	3	
Skin irritation: Mild		
Eye irritation: Severe		
Sensitation: Not considered an occupati	onal sensitizer	
Phosphoric Acid 7664-38-2		
Oral (LD 50): 1200 mg/kg - Rat		
Inhalation (LC 50): 25.5 mg/m3 - rat		
Skin irritation: Severe		
Eye irritation: Severe		
Sensitation: Not considered an occupati	onal sensitizer	
Diethylene glycol butyl ether 112-34-5		

Oral (LD 50): 5660 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Moderate

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer



Rust Remover

MSDS Number: B198

Revision Date: March 31, 2011

Page 4 of 5

12

ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

ORM-D

15

Ship in accordance with 49 CFR parts 100-185.

REGULATORY INFORMATION

COMPONENT / (CAS/PERCENT) / CODES

*Oxalic acid (144627 <10%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Phosphoric acid (7664382 <5%) CERCLA, CSWHS, EPCRAWPC, MASS, NJHS, OSHAWAC, SARA313, TSCA, TXAIR, WHMIS

*Diethylene Glycol Butyl Ether (112345 <4%) SARA313, TSCA, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EPCRAWPC = EPCRA Water Priority Chemicals MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TXAIR = TX Air Contaminants with Health Effects Screening Level WHMIS = Workplace Haz Mat Info Sys Canada



Rust Remover

MSDS Number: B198

16

Revision Date: March 31, 2011

Page 5 of 5

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

END OF MSDS DOCUMENT