

Power Strike

MSDS Number: S787

Revision Date: March 25, 2010

Page 1 of 4

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc. PROCHEM 325 S. Price Road Chandler, AZ 85224

Contact: Prochem Telephone Number: 480-899-7000 FAX Number: 480-786-9538 E-Mail: info@prochem.com Web www.prochem.com

Product Name:	Power Strike
Revision Date:	March 25, 2010
Version:	1.0
MSDS Number:	S787

Emergency Telephone: (800) 535-5053 [Infotrac]

2	HAZARDS IDENTIFICATION	
Route of Entry:	Eyes; Skin; Inhalation; Ingestion;	
Target Organs:	Eyes; Skin;	
Inhalation:	Minimal respiratory tract irritation may occur with exposure to a large amount of material.	
Skin Contact:	May Cause Irritation.	
Eye Contact:	May Cause Irritation.	
Ingestion:	Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.	
HMIS II-ratings (scale 0-4): Health = 2, Fire = 0, Reactivity = 0 HMIS Rating H2/F0/PH0®		

NFPA-ratings (scale 0-4): Health = 2, Fire = 0, Reactivity = 0

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
111762	1-10%	Ethylene Glycol Butyl Ether
497198	10-20%	Sodium Carbonate
6834920	1-10%	Sodium metasilicate

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.



Power Strike

MSDS Number: S787

Revision Date: March 25, 2010

Page 2 of 4

4	FIRST AID MEASURES
Inhalation:	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Skin Contact:	Wash with soap and water. If irritation persists consult medical personnel.
Eye Contact:	Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
Ingestion:	If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

MEASURES

Flash Point:

N/A

Wear self contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery.Sweep Up, Place In Bag and Hold For Waste Disposal. Ventilate Area and Wash Spill Site After Material Pickup is Complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7	HANDLING AND STORAGE	
Handling Precautions	Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.	
Storage Requirement	s: Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or acidic materials.	

Engineering Controls:Normal room ventilation is satisfactory for limited use.Protective Equipment:HMIS PP, B | Safety glasses, GlovesExposure Guidelines/Other:Ethylene glycol monobutyl ether 111-76-2 OSHA PEL 50 ppm - 240
mg/m3

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White		
Physical State:	Powder	Boiling Point:	N/D
Odor:	Citrus	Freezing/Melting Pt.:	N/D
pH:	10.5 - 11.5 @1% solution	Solubility:	Soluble
Vapor Pressure:	N/D	Spec Grav./Density:	N/A
Vapor Density:	N/D		

VOC:

8

9

8.5% concentrate 0.26% diluted



Power Strike

MSDS Number: S787

Revision Date: March 25, 2010

Page 3 of 4

10	STABILITY AND REACTIVITY	
Stability:		Product is stable under normal conditions.
Conditions to avoid:		None Known
Materials to avoid (in	compatability):	None Known
Hazardous Decompo	osition products:	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization: Will not occur.		Will not occur.
11	TOXICOLOGICAL INFORMATION	
Toxicity Data:		
Ethylene glycol butyl e	ther 111-76-2	
Oral (LD 50): 917 mg/kg - Rat		
Inhalation (LC 50): 2900 mg/m3/7H - Rat		
Skin irritation: Mild		

Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

Sodium Carbonate 497-19-8

Oral (LD 50): 4090 mg/kg - Rat

Inhalation (LC 50): 2300 mg/m3/2H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Moderate - Rabbit

Sensitation: Not considered an occupational sensitizer

Sodium Metasilicate 6834-92-0

Oral (LD 50): 1153 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

12

ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.



Power Strike

MSDS Number: S787

Revision Date: March 25, 2010

Page 4 of 4

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Ethylene Glycol Butyl Ether (111762 1-10%) HAP, MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Sodium Carbonate (497198 10-20%) TSCA, WHMIS

*Sodium metasilicate (6834920 1-10%) TSCA, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

HAP = Hazardous Air Pollutants MASS = MA Massachusetts Hazardous Substances List OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level WHMIS= Workforce Hazardous Material Information System

16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

END OF MSDS DOCUMENT