

## Heat Wave

MSDS Number: S778

Revision Date: March 25, 2010

Page 1 of 4

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer

Kärcher North America, Inc.  
PROCHEM  
325 S. Price Road  
Chandler, AZ 85224

Contact: Prochem  
Telephone Number: 480-899-7000  
FAX Number: 480-786-9538  
E-Mail: info@prochem.com  
Web www.prochem.com

Product Name: Heat Wave  
Revision Date: March 25, 2010  
MSDS Number: S778

Emergency Telephone: (800) 535-5053 [Infotrac]

### 2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation; Ingestion;  
Target Organs: Eyes; Skin;  
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.  
Skin Contact: May Cause Irritation.  
Eye Contact: May Cause Irritation.  
Ingestion: Small amounts swallowed incidental to normal handling operations are not likely to cause injury; swallowing amounts larger than that may cause temporary injury.

HMIS II-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0

HMIS Rating H2/F1/PH0®

NFPA-ratings (scale 0-4): Health = 2, Fire = 1, Reactivity = 0

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
112345	1-10%	Diethylene Glycol Butyl Ether
497198	15-25%	Sodium Carbonate
6834920	10-20%	Sodium metasilicate

OSHA Regulatory Status:

This MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

## Heat Wave

MSDS Number: S778

Revision Date: March 25, 2010

Page 2 of 4

### 4 FIRST AID MEASURES

**Inhalation:** If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.  
**Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.  
**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.  
**Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

### 5 FIRE FIGHTING MEASURES

**Flash Point:** N/A  
Wear self contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

### 6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Sweep up, place in bag and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

### 7 HANDLING AND STORAGE

**Handling Precautions:** Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage); wash thoroughly after handling.  
**Storage Requirements:** Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or acidic materials.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Normal room ventilation is satisfactory for limited use.  
**Protective Equipment:** HMIS PP, B | Safety glasses, Gloves  
**Exposure Guidelines/Other:** No OSHA PEL established for listed chemicals.

### 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Orange	<b>Boiling Point:</b>	N/D
<b>Physical State:</b>	Powder	<b>Freezing/Melting Pt.:</b>	N/D
<b>Odor:</b>	Floral/Lemon	<b>Solubility:</b>	Soluble
<b>pH:</b>	11.0 - 11.5 @1% Solution	<b>Spec Grav./Density:</b>	N/A
<b>Vapor Pressure:</b>	N/D		
<b>Vapor Density:</b>	N/D		

**VOC:** 3.5% LVP-VOC

## Heat Wave

MSDS Number: S778

Revision Date: March 25, 2010

Page 3 of 4

### 10 STABILITY AND REACTIVITY

<b>Stability:</b>	Product is stable under normal conditions.
<b>Conditions to avoid:</b>	None Known
<b>Materials to avoid (incompatibility):</b>	None Known
<b>Hazardous Decomposition products:</b>	Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
<b>Hazardous Polymerization:</b>	Will not occur.

### 11 TOXICOLOGICAL INFORMATION

#### Toxicity Data:

Diethylene glycol butyl ether 112-34-5

Oral ( LD 50): 5660 mg/kg - Rat

Inhalation ( LC 50): Not listed on RTECS

Skin irritation: Moderate

Eye irritation: Severe

Sensitization: Not considered an occupational sensitizer

Sodium Carbonate 497-19-8

Oral ( LD 50): 4090 mg/kg - Rat

Inhalation ( LC 50): 2300 mg/m<sup>3</sup>/2H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Moderate - Rabbit

Sensitization: Not considered an occupational sensitizer

Sodium Metasilicate 6834-92-0

Oral ( LD 50): 1153 mg/kg - Rat

Inhalation ( LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

Sensitization: Not considered an occupational sensitizer

### 12 ECOLOGICAL INFORMATION

Refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

## Heat Wave

MSDS Number: S778

Revision Date: March 25, 2010

Page 4 of 4

### 13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

### 14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

### 15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

-----  
\*Diethylene Glycol Butyl Ether (112345 1-10%) HAP, SARA313, TSCA, WHMIS

\*Sodium Carbonate (497198 15-25%) TSCA, WHMIS

\*Sodium metasilicate (6834920 10-20%) TSCA, WHMIS

REGULATORY KEY DESCRIPTIONS

-----  
All components are listed on TSCA

HAP = Hazardous Air Pollutants

SARA313 = SARA 313 Title III Toxic Chemicals

WHMIS = workplace Haz Mat Info Sys Canada

### 16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000

**END OF MSDS DOCUMENT**