

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: OLEOSA WITH PROTECTION  
CL040, CL042

## SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 542 West Confluence Ave, Salt Lake City, Utah 84123  
Company Phone Number: 801-261-1282  
Emergency Phone Number: 1-800-535-5053 (Infotrac)  
Date Prepared: 4-9-05 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

Fire: Health: Reactivity:

## 2. COMPOSITION/ INFORMATION ON INGREDIENTS

Contains no hazardous ingredients above reportable thresholds

## 3. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

Prolonged or repeated contact may cause irritation of skin and eyes.

ROUTE(S) OF ENTRY.....: Skin and eye contact with liquid.

CARCINOGENICITY:

NTP.....: No

IARC.....: No

OSHA.....: No

## 4. FIRST AID MEASURES:

SKIN.....: Remove contaminated clothing and shoes. Wash with soap or mild detergent and large amounts of water. Do not use solvents or thinners.

EYES.....: Hold eyes open and flush for at least 15 minutes with large amounts of water. Consult physician if irritation occurs.

INGESTION.: Do not induce vomiting. Give two glasses of water to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician immediately.

INHALATION: No inhalation hazards are anticipated for this product

## **5. FIRE FIGHTING MEASURES**

FLASH POINT.....: Not applicable

EXTINGUISHING MEDIA...Alcohol foam, carbon dioxide, dry powder, or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing.

## **6. ACCIDENTAL RELEASE MEASURES:**

SPILL AND LEAK PROCEDURES: Contain spills onto inert absorbent and place in suitable containers.

## **7. HANDLING AND STORAGE**

STORAGE: Store closed containers in cool, dry area away from heat, direct sunlight, oxidizing agents, and strong acids and alkalis.

HANDLING: Avoid skin and eye contact. Do not eat, drink or smoke in area.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

ENGINEERING CONTROLS: Use in a well ventilated area.

RESPIRATORY PROTECTION: Not required.

SKIN PROTECTION: Clothing suitable to prevent skin contact.  
Use butyl rubber gloves. Check suitability recommendations by protective equipment manufacturers, especially towards chemical breakthrough resistance.

EYE PROTECTION: Safety goggles with side shields.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

PHYSICAL FORM: .....	Pale Yellow Liquid
ODOR: .....	Characteristic
pH	7-10
BOILING POINT: .....	>212 °F (>100°C)
FLASH POINT	212 °F (100°C)
AUTO IGNITION: .....	>470°F(>250°C)
VAPOR PRESSURE: .....	Not available
DENSITY: .....	~0.8 g/ml(25 °C)
VAPOR DENSITY	Not available
SOLUBILITY IN WATER	SOLUBLE

## **10. STABILITY AND REACTIVITY**

CHEMICAL STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other potentially toxic fumes.

POLYMERIZATION: Will not occur under regular conditions of use.

INCOMPATIBILITIES: Avoid strong acids, bases, and oxidizing agents.

## **11. TOXICOLOGICAL INFORMATION**

Believe to be practically non toxic.

## **12. ECOLOGICAL INFORMATION**

Avoid contamination of ground water or waterways. Do not discharge into sewers.

## **13. DISPOSAL CONSIDERATIONS**

Incinerate or dispose of in accordance with Federal, State or Local regulations.

## **14. TRANSPORT INFORMATION**

DOT SHIPPING NAME Not regulated.

## **15. REGULATORY INFORMATION**

All components of this product are on the TSCA Inventory.

SARA Title III:

To the best of our knowledge this product contains **no** toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

**Note:** Entries under this section cover only those regulations typically addressed in the MSDS generating process, such as, TSCA, and EPCRA/SARA Title III.

## **16. OTHER INFORMATION**

HAZCOM LABEL: CAUTION: PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION

---

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

---

N/A = Not applicable N/D = Not determined N/E = Not established