MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SOFT REMOVER CL064, CL066

SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 542 West Confluence Ave, Salt Lake City, Utah 84123

Company Phone Number: 801-261-1282

Emergency Phone Number: 1-800-535-5053 (Infotrac)

Date Prepared: 4-9-05 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

Fire: Health: Reactivity:

2. COMPOSITION/ INFORMATION ON INGREDIENTS

<u>Component</u>	CAS#	% By Wt	Exposure Limits
Acetone	67-64-1	>25	500 ppm TWA ACGIH
Ethyl Alcohol	64-17-5	>20-<40	1000 ppm TWA-ACGIH
Methyl alcohol	67-56-1	>1-<5	200 ppm TWA ACGIH

3. <u>HAZARD IDENTIFICATION</u>

POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY.....: Skin and eye contact with liquids or inhalation of vapor or aerosol

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

Ethyl alcohol is an irritant to skin, eyes and respiratory passages. Overexposure may cause headache, dizziness, drowsiness and nausea.

Acetone is an irritant to skin, eyes and respiratory passages. Overexposure may cause loss of coordination, headache, dizziness, drowsiness, nausea, kidney and liver damage and blood disorders.

Methanol is toxic by inhalation or ingestion. May be fatal or cause blindness if ingested. May cause central nervous system depression. May cause liver, kidney and heart damage. Caused adverse reproductive and fetal effects in animals.

Irritant to skin, eyes and respiratory passages. May cause nausea, vomiting and diarrhea.

CARCINOGENICITY:

NTP.....: No IARC...: No OSHA...: No

4. FIRST AID MEASURES:

SKIN.....: Remove contaminated clothing and shoes. Wash with soap or mild detergent and large amounts of water. Do not use solvents or thinners. Get medical attention.

EYES....... Hold eyes open and flush for at least 15 minutes with large amounts of water. Seek immediate medical attention.

INGESTION.: Do not induce vomiting. Give two glasses of water to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician immediately.

INHALATION: Remove to fresh air immediately. If breathing is difficult administer oxygen. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT..... 40 °F (5°C)

EXTINGUISHING MEDIA... Alcohol foam, carbon dioxide, dry powder, or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing. Fight fire from a safe distance due to explosion hazard

6. ACCIDENTAL RELEASE MEASURES:

SPILL AND LEAK PROCEDURES: Remove all sources of ignition. Wear appropriate personal protective equipment; contain spills onto inert absorbent and place in suitable containers.

7. HANDLING AND STORAGE

STORAGE: Store closed containers in cool, dry area away from heat, direct sunlight, oxidizing agents, and strong acids and alkalis. Keep in a well-ventilated area suitable for flammable material storage.

HANDLING: Avoid skin and eye contact. Do not eat, drink or smoke in application area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Use local exhaust ventilation. Use in an area with controls and equipment suitable for handling flammable liquids.

RESPIRATORY PROTECTION: If airborne concentration exceeds recommended limits, use a NIOSH approved respirator in accordance with OSHA Respirator Protection requirements under 29 CFR 1910.134.

SKIN PROTECTION: Clothing suitable to prevent skin contact. Use butyl rubber gloves. Check suitability recommendations by protective equipment manufacturers, especially towards chemical breakthrough resistance.

EYE PROTECTION: Safety goggles with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Liquid

ODOR: Characteristic alcohol

PH NA

BOILING POINT: >131 °F (55°C)
AUTOIGNITION Not available
VAPOR PRESSURE: 23 mbar @ 25 °C
DENSITY: 1.0 g/ml(25 °C)

SOLUBILITY IN WATER Miscible VAPOR DENSITY >air

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other potentially toxic fumes.

POLYMERIZATION: Will not occur under regular conditions of use.

INCOMPATIBILITIES: Avoid strong acids, bases, and oxidizing agents.

11. TOXICOLOGICAL INFORMATION

See Section 3 - Human Effects and Symptoms of Overexposure

12. ECOLOGICAL INFORMATION

Avoid contamination of ground water or waterways. Do not discharge into sewers.

13. <u>DISPOSAL CONSIDERATIONS</u>

Incinerate or dispose of in accordance with Federal, State or Local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME..: FLAMMABLE LIQUID, N.O.S.

(Contains acetone and ethyl alcohol) Class 3, UN 1993, Packing group II

15. REGULATORY INFORMATION

All components of this product are on the TSCA Inventory.

SARA Title III:

Methanol is subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

Note: Entries under this section cover only those regulations typically addressed in the MSDS generating process, such as, TSCA, and EPCRA/SARA Title III.

16. OTHER INFORMATION

HAZCOM LABEL: WARNING FLAMMABLE LIQUID AND VAPOR CAUTION! IRRITANT TO SKIN, EYES AND RESPRIATORY PASSAGES. HARMFULL IF SWALLOWED, ABSORBED THROUGH SKIN, OR INHALED. MAY CAUSE HEADACHE, NAUSEA, VOMITING, DIZZINESS AND DROWSINESS.

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A = Not applicable N/D = Not determined N/E = Not established