

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: NUBUCK FOAM CLEANER
CL038

SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 542 West Confluence Ave, Salt Lake City, Utah 84123
Company Phone Number: 801-261-1282
Emergency Phone Number: 1-800-535-5053 (Infotrac)
Date Prepared: 4-9-05 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)
Fire: Health: Reactivity:

2. COMPOSITION/ INFORMATION ON INGREDIENTS

Component	CAS#	% By Wt.	Exposure Limits
Butane	106-97-8	10 – 25	800 ppm TWA ACGIH
Propane	74-98-6	10 - 25	2500 ppm TWA ACGIH

3. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

ROUTE(S) OF ENTRY.....: Skin and eye contact with liquids or inhalation of vapor or aerosol

HUMAN EFFECTS AND SYMPTOMS OF OVEREXPOSURE:

Butane may cause narcosis and overexposure to propane may cause asphyxiation.

Propane overexposure may cause asphyxiation

CARCINOGENICITY:

NTP.....: No

IARC.....: No

OSHA.....: No

4. FIRST AID MEASURES:

SKIN.....: Remove contaminated clothing and shoes. Wash with soap or mild detergent and large amounts of water. Do not use solvents or thinners. Get medical attention.

EYES.....: Hold eyes open and flush for at least 15 minutes with large amounts of water. Seek immediate medical attention.

INGESTION.: Do not induce vomiting. Give two glasses of water to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician immediately.

INHALATION: Remove to fresh air immediately. If breathing is difficult administer oxygen. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT.....: NA

EXTINGUISHING MEDIA... Alcohol foam, carbon dioxide, dry powder, or water spray.

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing. Fight fire from a safe distance due to explosion hazard

6. ACCIDENTAL RELEASE MEASURES:

SPILL AND LEAK PROCEDURES: Remove all sources of ignition. Wear appropriate personal protective equipment; contain spills onto inert absorbent and place in suitable containers.

7. HANDLING AND STORAGE

STORAGE: Store closed containers in cool, dry area away from heat, direct sunlight. Keep in a well-ventilated area suitable for flammable material storage.

HANDLING: Avoid skin and eye contact. Do not eat, drink or smoke in application area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Use local exhaust ventilation. Use in an area with controls and equipment suitable for handling flammable liquids.

RESPIRATORY PROTECTION: If airborne concentration exceeds recommended limits, use a NIOSH approved respirator in accordance with OSHA Respirator Protection requirements under 29 CFR 1910.134.

SKIN PROTECTION: Clothing suitable to prevent skin contact.
Use butyl rubber gloves. Check suitability recommendations by protective equipment manufacturers, especially towards chemical breakthrough resistance.

EYE PROTECTION: Safety goggles with side shields.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM: Aerosol, colorless
ODOR: Characteristic
PH: Not applicable
AUTOIGNITION: Not available
SOLUBILITY IN WATER: Partially, active substance

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, and other potentially toxic fumes.

POLYMERIZATION: Will not occur under regular conditions of use.

INCOMPATIBILITIES: Avoid strong acids, bases, and oxidizing agents.

11. TOXICOLOGICAL INFORMATION

See Section 3 - Human Effects and Symptoms of Overexposure

12. ECOLOGICAL INFORMATION

Avoid contamination of ground water or waterways. Do not discharge into sewers.

13. DISPOSAL CONSIDERATIONS

Incinerate or dispose of in accordance with Federal, State or Local regulations.

14. TRANSPORT INFORMATION

DOT SHIPPING NAME: AEROSOLS
Class 2, UN 1950

15. REGULATORY INFORMATION

All components are on the TSCA Inventory.

SARA Title III:

To the best of our knowledge this product contains **no** toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

Note: Entries under this section cover only those regulations typically addressed in the MSDS generating process, such as, TSCA, and EPCRA/SARA Title III.

16. OTHER INFORMATION

PRODUCT LABEL SUMMARY: DANGER: EXTREMELY FLAMMABLE.
CONTENES UNDER PRESSURE
IRRITANT TO SKIN, EYES AND RESPIRATORY PASSAGES.
HARMFUL IF SWALLOWED
KEEP OUT OF REACH OF CHILDREN.

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.

N/A = Not applicable N/D = Not determined N/E = Not established