

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: SOLVENT CLEAN CS11

SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 542 West Confluence Ave, Salt Lake City, Utah 84123

Company Phone Number: 801-261-1282

Emergency Phone Number: 1-800-535-5053 (Infotrac)

Date Prepared: 1-20-06 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)

Fire: 2 Health: 2 Reactivity: 0

SECTION 2: INGREDIENTS

PRINCIPLE HAZARDOUS INGREDIENTS:	<u>OSHA</u>	<u>TLV</u>	<u>%</u>
Dipropylene glycol monomethyl ether (CAS #34590-94-8)	100 ppm	100 ppm	40-55
Odorless Mineral Spirit (CAS #64742-48-9)	300 ppm	N/D	40-55

SECTION 3: PHYSICAL DATA

Boiling Point (°F) 360°	Specific Gravity(H ₂ O=1) N/E
Vapor Pressure (mmHg.) N/E	Percent Volatile by Volume 80-100%
Vapor Density (AIR=1) N/E	PH (1% Solution)N/A
Solubility in WaterN/E	

Appearance & Odor......Clear liquid with slight ether odor

SECTION 4: FIRE, EXPLOSION & REACTIVITY DATA

Flash Point: 137° F

Extinguishing Media: Water fog or fine spray, carbon dioxide, dry chemical, foam

Special Fire Fighting Procedures: Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers - do not use direct water stream. Wear positive pressure self-contained breathing apparatus & complete protective clothing.

Unusual Fire and Explosion Hazards: COMBUSTIBLE! Keep container tightly closed. Applying to hot surfaces requires special precautions. Empty container very hazardous - do not drill, solder cut, etc. Material can accumulate static charge which can cause electrical discharge.

Stability: Stable

Chemical Incompatibility: Avoid contact with oxidizing agents

Hazardous Decomposition or Byproducts: Carbon Monoxide, Carbon Dioxide from burning.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Isolate from oxidizers, heat, and open flame. Do not store in direct sunlight

SECTION 5: HEALTH HAZARD INFORMATION

Route(s) of entry Eyes? No Skin? No Inhalation? Yes Ingestion? Yes

Health Hazards: Eyes –May cause irritation Skin –May cause irritation

Inhalation – Prolonged contact with high vapor/aerosol concentrations are irritating to the

respiratory tract. May cause headaches, dizziness,

drowsiness, unconsciousness, and other **serious** central nervous system effects. Ingestion – **Harmful or fatal if swallowed**. Can cause abdominal irritation, nausea,

vomiting, diarrhea and mild to severe pulmonary injury.

Carcinoginicity: NTP? No OSHA? No IARC Monograph? No

SECTION 6: EMERGENCY AND FIRST AID PROCEDURES

Eyes...... Flush with water for 15 minutes and get medical attention.

Skin....... Immediately remove contaminated clothing - launder before wearing. Flush with large amounts

of water. Wash with soap and water.

Inhalation.. Remove to fresh air. Administer artificial respiration if breathing has stopped.

Get medical attention.

Ingestion... Get IMMEDIATE medical attention! Do NOT induce vomiting. Keep

person at rest.

SECTION 7: PRECAUTIONS FOR SAFE HANDLING AND USE

Respiratory Protection... Respirator recommended
Protective Clothing...... Rubber gloves recommended.

Eye Protection...... Safety goggles or safety glasses with side shields recommended.

Ventilation...... Mechanically assisted ventilation recommended.

or weld. Empty container very hazardous! Keep container tightly closed and upright when not in use to prevent leakage. Store in cool, well ventilated place away from incompatible materials. Do not handle or store near an open flame, heat or other source of ignition. Do not store in direct sunlight.

SECTION 8: SPILL OR LEAK PROCEDURES AND WASTE DISPOSAL

Wear recommended safety equipment. Keep all sources of ignition away from spill. If indoors, ventilate area of spill. Keep out of drains, sewers or waterways. Use sand or other inert material to contain spill then collect for reuse or disposal. Do not flush with water. **All disposals must be in accordance with all federal, state and local regulations.**

While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy. BRIDGEPOINT SYSTEMS MAKES NO WARRANTY WITH RESPECT HERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON. Users must determine safe conditions for use and assume liability for any loss, injury, damage or expense resulting from use of this product.